

GENERAL CATALOG

FOR MORE INFORMATION PLEASE CONTACT:



BHAGWATI
Hardware & Mill Store Since 1976

Address: 4769, 1ST Floor, Old Post Office Building,
Hauz Qazi, Delhi - 110006
Mobile: 9212012856, 9350076343
Website: www.bhagwathardware.com
www.bhagwathardwaredelhi.in
E-mail: sandeep@bhagwatimail.com

AN ISO 9001 : 2015 CERTIFIED COMPANY

CEDAR®

Digital torque Wrench**DIW-15/20/75/120****Various functions Display section one apparatus**

Yes-no decision conditions etc. can save five channels.

.. A channel is only changed even if bolting conditions change.

It is not necessary to reset up a maximum value and a minimum value one by one like former.



- Ergonomic, light weight, rugged metal construction
- Wrench head swivels 300°
- Peak, Real Time and Peak Down measuring mode (selectable)
- 800 data memory
- Programmable High and Low set points with both audible beep and Green/ Red LED indicator for uniform torque tightening or GO/NO GO testing
- Both CW and CCW operation
- USB output (ASCII format)
- Runs on internal Ni-MH batteries (12 hour use)
- CW step less one-way clutch adapter or clutch adapter, AC charger included.

Specification

MODEL		DIW-15	DIW-20	DIW-75	DIW-120
Accuracy guarantee range	N/m	0.20~15	0.20~20	0.20~75	2.0~120
	kgf/cm	2.0~150	2.0~200	2.0~750	20~1200
	lbf/in	2.0~130	2.0~174	2.0~651	20~1040
Accuracy		Reading ±0.5% (199 or less digit±1 digit)	Reading ±0.5% (499 or less digit±3digit)		Reading ±0.5% (199 or less digit±1 digit)
Display		The 4 figures digital display of LCD			
Measurement direction		CW-CCW (right and left)			
Measurement Mode	PP	peak to peak The highest value of load is hold-displayed.			
	TR	track A display also changes with load change.			
	PD	peak-down Load catches and displays the moment included in descent from a rise.			
	C	Real-time Output Load torque value is outputted every about1/160 second.			
A success or failure judging function		High and low value are measurement within the limits, and can be set up. Five-set preservation is possible.			
The Maximum, minimum, and the average value		The data number, the maximum, the minimum value, and the average value of memory data are displayed.			
Data memory counts		800 data			
Data output		ASCII format (baud rate 19200)			
auto clear time		If the set-up time comes, measurement value will be automatically cleared in 0.0~3.0 seconds (0.5s interval).			
Setup of count		1 to 99 count (count in a clockwise direction)			
Power supply		Ni-MH chargeable battery 1.2V×4cells 800mAh			
Charge time / use time		Charge 5 hour /, continuation about 12-hour use			
Auto-power-off		After the neglect during 10 minutes			
Bit / Socket part		□6.35	□9.5		□12.7
Weight (about)		430g	470g	620g	830g
Accessories (one piece each)		one-way clutch adapter or clutch adapter			
		Exclusive charger			
		Result of calibration document Certification on calibration document / Traceability system figure			
Option		When outputting data, the USB cable (mini B) is needed.			

FOR MORE INFORMATION PLEASE CONTACT:



BHAGWATI

Hardware & Mill Store Since 1976

Address: 4769, 1ST Floor, Old Post Office Building,
Hauz Qazi, Delhi - 110006

Mobile: 9212012856, 9350076343

Website: www.bhagwathardware.com
www.bhagwathardwaredelhi.in

E-mail: sandeep@bhagwatimail.com

AN ISO 9001 : 2015 CERTIFIED COMPANY